

eTC-2300



The Tiny One

The smallest Thin Client for network boot or with optional Linux eLux NG. Ideal because of its minimal need of space, low power consumption and fanless operation. Small-sized, but completely equipped with 200 Mhz CPU, 128 MB RAM, 3xUSB, CF-slot, audio port and high-resolution graphics card as well as all common interfaces. With support of PXE (network boot) it is particularly suitable for Linux mini distributions like ThinStation, PXES, LTSP etc. It even allows the installation of a 2,5" harddisk and is ready to be mounted to the back of a monitor (VESA mount included). Also suitable as an embedded PC.

Boots from:

- CompactFlash (equipped with CF-slot)
- internal flash card (option)
- USB-Stick (not included)
- external devices (not included)
- internal HDD (not included)
- over the network (PXE)

Technical Specifications

CPU: Vortex86 SoC 200 MHz

RAM: 128 MByte SDRAM, onboard

Chipset: SiS 550

Graphics card: Shared system memory area 8MB, onboard

Sound card: AC97 CODEC V2.1, onboard

LAN: Realtek 8100B single chip x 1: 10/100 Mbps

USB 1.1: 3

Seriell ports: 2 (optional)

PS/2: 1 (Y-cable for keyboard and mouse is included)

Type I/II Compact Flash slot: 1

Adapter IDE for Flash Memory (DOM): 1

Harddisk: Installation kit for 1 x 2,5" included

Power supply: 15 W extern (included)

eTC-2300

VESA mount: included
Size: 115 x 115 x 35 mm
Weight: 505 gr

Price : € 153,51 inc VAT (€ 129,00 ex VAT)

Options available for eTC-2300 :

Operating System

-, 128 MB Flash with Linux eLux NG (+€ 46,41).

addl. interface

Mini PCI (+€ 7,14), -, 2 x serial port (RS-232) (+€ 23,80).

EPATec